UL Product iQ™



ZPMV8.E324220 - Wiring, Printed Certified for Canada - Component

Wiring, Printed Certified for Canada - Component

GLOBAL SUCCESS CIRCUITS CO LTD

E324220

Second-Period Of Industrial Park Wan'An County Ji'an, JiangXi 343800 China

	Cond Width			Max					Max					
Туре	Min mm(in)	Min Edge mm(in)	Cond Thk mic(mil)	SS/ DS/ DSO	Area Diam mm(in)	Solder Limits		Assembly Solder Process (IPC)		Oper		Meets UL796		
						.c	sec	·c	Cycles	·c	Class	DSR	1	
Multilayer	printed wi	ring board	•											
G- 2(Note1)	0.1 (0.004)	0.3 (0.012)	34 (1.34) Int:204	DS	50.8 (2)	288	20			130	V-0	All		
W-2	0.075 (0.003)	0.15 (0.006)	17 (0.67) Int:68	DS	50.8 (2)	288	20			130	V-0	All		
Single lay	er metal ba	se printed	wiring board	s										
AL01	0.22 (0.009)	0.26 (0.01)	34 (1.34)	ss	50.8 (2)	288	20	-		90	V-0	All	0	
Single lay	er printed v	viring boar	ds										_	
T-1	0.075 (0.003)	0.15 (0.006)	17 (0.67)	DS	50.8	288	20		-	130	V-0	All		

^{* -} CTI marking is optional and may be marked on the printed wiring board.

Note1 -& - When the external copper thickness is 34-102mic, the midboard and edge conductor width is 0.10mm and 0.30mm. When the external copper thickness is 102-204mic, the midboard conductor width is 0.40mm, the edge conductor width is 0.42mm.

Marking: Company name or tradename "E324220" or trademark



type designation and the Recognized Component

Mark for Canada, C . May be followed by a suf

May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-07-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.