

## ZPMV2.E324220 - Wiring, Printed - Component

## Wiring, Printed - Component

## GLOBAL SUCCESS CIRCUITS CO LTD

Second-Period Of Industrial Park  
Wan'An County  
Ji'an, JiangXi 343800 China

E324220

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Area Diam mm(in)	Solder Limits °C sec	Assembly			Max Oper Temp °C	Meets Flame Class	C UL796 DSR	T I
	Min	Edge					Solder	Solder	Process				
	mm(in)	mm(in)					°C	°C	(IPC) Cycles				
<b>Multilayer printed wiring boards</b>													
<b>G-2</b> (Note 1)	0.1 (0.004)	0.3 (0.012)	34 (1.34) Int:204	DS	50.8 (2)	288	20	-	-	130	V-0	All	*
<b>W-2</b>	0.075 (0.003)	0.15 (0.006)	17 (0.67) Int:68	DS	50.8 (2)	288	20	-	-	130	V-0	All	*
<b>Single layer metal base printed wiring boards</b>													
<b>AL01</b>	0.22 (0.009)	0.26 (0.01)	34 (1.34)	SS	50.8 (2)	288	20	-	-	90	V-0	All	0
<b>AL02</b>	0.15 (0.006)	0.2 (0.008)	28 (1.1)	SS	50.8 (2)	288	20	-	-	130	V-0	All	0
<b>Single layer printed wiring boards</b>													
<b>T-1</b>	0.075 (0.003)	0.15 (0.006)	17 (0.67)	DS	50.8 (2)	288	20	-	-	130	V-0	All	*

\* - CTI marking is optional and may be marked on the printed wiring board.

Note1 -& - When the external copper thickness is 34-102mic,the midboard and edge conductor width is 0.10mm and 0.30mm.When the external copper thickness is 102-204mic,the midboard conductor width is 0.40mm,the edge conductor width is 0.42mm.

Marking: Company name or tradename "E324220" or trademark  , type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-07-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.